


## DIMMER COMPATIBILITY PAR16

### BASIC INFORMATION:

#### 1. WHAT IS THE PRODUCT CODE AND WHERE DO I FIND IT?

The product code describes the lamp type. It contains 7 letters and digits and is starting with "A". Below an example for the product code of the stamp of the lamp:



#### 2. HOW CAN I READ THE FOLLOWING CHARTS?

Legend:  
Information about the dimmability of the lamps. Green means very good dimmability, yellow means limited dimmability, red means undesired dimmability etc.

List of dimmers tested in laboratory conditions

Legend					SUPERSTAR PAR16 35 36°				SUPERSTAR PAR16 50 36°				SUPERSTAR PAR16 80 36°				SUPERSTAR PAR16 80 120°			
Very good dimmability with indicated number of lamps (dimming range greater than 75%)																				
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)																				
Undesired dimmability																				
Not relevant																				
Not tested																				
EAN/Basic Code					4052839330153/AC01184				405283933017/AC01187				4052839330218/AB41905				405807503658/AC03043			
EAN/Basic Code					4052839330157/AC01182				4052839330195/AC01184				4052839330232/AB41906				405807503658/AC03051			
Dimmer					Number of Lamps		Dimming range		Number of Lamps		Dimming range		Number of Lamps		Dimming range		Number of Lamps		Dimming range	
ABB	STD 50-3	230/50Hz	60-500	L	1-20	98% - 15%	1-13	98% - 20%	1-8	97% - 23%	1-8	97% - 23%	1-20	98% - 15%	2-20	97% - 12%	2-20	98% - 16%	2-20	98% - 16%
Altenburger Electronic	50_30	230/50Hz	15-350	T	1-10	98% - 15%	2-10	97% - 12%	1-4	96% - 1%	1-4	96% - 1%	1-10	98% - 15%	2-10	97% - 12%	1-4	96% - 1%	1-4	96% - 1%
ALPORA	DSP 400	230/50Hz	400	L	1-20	98% - 27%	1-20	98% - 26%	1-20	97% - 27%	1-20	97% - 27%	1-20	98% - 1%	2-9	98% - 1%	1-6	97% - 9%	1-6	97% - 9%
Berker	2861	230/50Hz	50-420	U	1-15	98% - 1%	1-10	97% - 5%	1-6	94% - 7%	1-6	94% - 7%	1-15	98% - 1%	2-9	98% - 1%	1-6	97% - 9%	1-6	97% - 9%
Blicino	LNNT441N	230/50Hz			3-19	99% - 19%	2-12	97% - 19%	1-8	95% - 22%	1-8	95% - 22%	2-20	99% - 15%	2-20	98% - 17%	2-20	98% - 21%	2-20	98% - 21%
Blicino	LNNT4408	230/50Hz			1-10	96% - 22%	1-10	97% - 26%	1-10	96% - 22%	1-10	96% - 22%	1-10	96% - 22%	2-14	98% - 16%	1-9	97% - 15%	1-9	97% - 15%
Blicino	NT4402N	230/50Hz	500	R	1-13	98% - 34%	1-10	97% - 35%	1-5	97% - 15%	1-5	97% - 15%	1-20	98% - 15%	1-13	98% - 20%	1-8	97% - 23%	1-8	97% - 23%
Busch-Jaeger	6513 U-102	230/50Hz	40-420	T	2-13	98% - 1%	1-10	98% - 5%	1-6	97% - 9%	1-6	97% - 9%	2-20	98% - 1%	1-10	98% - 5%	1-5	99% - 7%	1-5	99% - 7%
Busch-Jaeger	6523 U-102	230/50Hz	420	T	1-11	98% - 1%	1-10	98% - 1%	1-5	99% - 7%	1-5	99% - 7%	1-10	98% - 1%	1-10	98% - 1%	1-4	97% - 1%	1-4	97% - 1%
Busch-Jaeger	2250 U	230/50Hz	60-600	L	1-10	98% - 6%	1-20	98% - 7%	1-20	97% - 10%	1-20	97% - 10%	1-10	98% - 1%	1-13	97% - 1%	1-8	96% - 1%	1-8	96% - 1%
Busch-Jaeger	6526 U	230/50Hz			1-20	98% - 1%	1-13	97% - 1%	1-8	96% - 1%	1-8	96% - 1%	1-10	98% - 1%	1-13	97% - 4%	1-10	97% - 19%	1-10	97% - 19%
Busch-Jaeger	2247 U-500	230/50Hz			1-14	98% - 1%	1-13	97% - 4%	1-10	97% - 19%	1-10	97% - 19%								
CENTURY CONTROL	MULTI DIMMER	230/50Hz	60-600	L																
DINUY	RE EL1LE1	230/50Hz	400	LED																
ELKO	400GLI	230/50Hz																		
ELKO	315GLE	230/50Hz	20-315	T																
ELKO	600GLI	230/50Hz	40-600	U																
ELKO	420GLEI	230/50Hz	40-420	U																

Information about the OSRAM lamp type

Assessment of the results into categories. Includes the number of lamps and the related dimming range

# DIMMER KOMPATIBILITÄT PAR16

## BASISINFORMATIONEN:

### 1. WAS IST DER PRODUKTCODE UND WO FINDE ICH IHN?

Der Produktcode beschreibt den Lampentyp. Er besteht aus sieben Buchstaben und Ziffern und beginnt mit einem "A". Nachfolgend ein Beispiel eines Produktcodes auf dem Aufdruck der Lampe.



220-240V **AC01770** 2700K  
 13 W 50/60 Hz 27 mA  
 Made in Germany XXX-XXXX

### 2. WIE LESE ICH DIE FOLGENDEN TABELLEN?

Legende: Angaben zur Dimmbarkeit der Lampen. Grün bedeutet eine sehr gute Dimmbarkeit mit der angegebenen Lampenanzahl, gelb bedeutet eine eingeschränkte Dimmbarkeit, rot bedeutet, dass unerwünschte dimmverhalten auftreten kann etc.









Liste der getesteten Dimmer

Legend					SUPERSTAR PAR16 35 36*				SUPERSTAR PAR16 50 36*				SUPERSTAR PAR16 60 36*				SUPERSTAR PAR16 60 120*			
Very good dimmability with indicated number of lamps (dimming range greater than 75%)																				
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)																				
Undesired dimmability																				
Not relevant																				
Not tested																				
Dimmer					EAN/Basic Code				EAN/Basic Code				EAN/Basic Code				EAN/Basic Code			
Brand	Model	Voltage range	Power	Type	405283330133/AC01184 405283330157/AC01192				405283330171/AC01187 405283330199/AC01194				405283330210/AB41305 405283330232/AB41306				405807503688/AC03049 405807503632/AC03051			
					Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range		
ABB	STD 50-3	230V50Hz	60-500	L	1-20	98% - 15%	1-13	98% - 20%	1-8	97% - 23%	1-8	97% - 23%	1-8	97% - 23%	1-8	97% - 23%	1-8	97% - 23%		
Altenburger Electronic	50 30	230V50Hz	15-350	T	2-20	98% - 15%	2-20	97% - 12%	2-20	98% - 16%	2-20	98% - 16%	2-20	98% - 16%	2-20	98% - 16%	2-20	98% - 16%		
AURORA	DSP 400	230V50Hz	400	L	1-10	98% - 15%	2-10	97% - 14%	1-4	96% - 1%	1-4	96% - 1%	1-4	96% - 1%	1-4	96% - 1%	1-4	96% - 1%		
Berker	2861	230V50Hz	50-420	U	1-20	98% - 27%	1-20	98% - 26%	1-20	97% - 27%	1-20	97% - 27%	1-20	97% - 27%	1-20	97% - 27%	1-20	97% - 27%		
Bicimo	LJNNT441N	230V50Hz			1-15	98% - 1%	1-10	97% - 5%	1-6	94% - 7%	1-6	94% - 7%	1-6	94% - 7%	1-6	94% - 7%	1-6	94% - 7%		
Bicimo	LJNNT4408	230V50Hz			2-20	98% - 1%	2-9	98% - 1%	1-6	97% - 3%	1-6	97% - 3%	1-6	97% - 3%	1-6	97% - 3%	1-6	97% - 3%		
Bicimo	NT4402N	230V50Hz	500	R	3-18	99% - 19%	2-12	97% - 19%	1-8	95% - 22%	1-8	95% - 22%	1-8	95% - 22%	1-8	95% - 22%	1-8	95% - 22%		
Busch-Jaeger	6513 U-102	230V50Hz	40-420	T	2-20	98% - 15%	2-20	98% - 17%	2-20	98% - 21%	2-20	98% - 21%	2-20	98% - 21%	2-20	98% - 21%	2-20	98% - 21%		
Busch-Jaeger	6523 U-102	230V50Hz	420	T	1-10	96% - 22%	1-10	97% - 26%	1-10	97% - 26%	1-10	97% - 26%	1-10	97% - 26%	1-10	97% - 26%	1-10	97% - 26%		
Busch-Jaeger	2250 U	230V50Hz	60-600	L	1-10	98% - 34%	2-14	98% - 16%	1-9	97% - 15%	1-9	97% - 15%	1-9	97% - 15%	1-9	97% - 15%	1-9	97% - 15%		
Busch-Jaeger	6526 U	230V50Hz			1-13	98% - 1%	1-10	97% - 3%	1-5	97% - 1%	1-5	97% - 1%	1-5	97% - 1%	1-5	97% - 1%	1-5	97% - 1%		
Busch-Jaeger	2247 U-500	230V50Hz			1-20	98% - 15%	1-13	98% - 20%	1-8	97% - 23%	1-8	97% - 23%	1-8	97% - 23%	1-8	97% - 23%	1-8	97% - 23%		
CENTURY CONTROL	MULTI DIMMER	230V50Hz	60-600	L	2-13	98% - 1%	1-10	98% - 5%	1-6	97% - 9%	1-6	97% - 9%	1-6	97% - 9%	1-6	97% - 9%	1-6	97% - 9%		
DINJY	RE EL1LE1	230V50Hz	400	LED	1-11	98% - 1%	1-10	98% - 1%	1-5	99% - 7%	1-5	99% - 7%	1-5	99% - 7%	1-5	99% - 7%	1-5	99% - 7%		
ELKO	400GLI	230V50Hz			1-10	98% - 1%	1-10	97% - 1%	1-4	97% - 1%	1-4	97% - 1%	1-4	97% - 1%	1-4	97% - 1%	1-4	97% - 1%		
ELKO	316GLE	230V50Hz	20-315	T	2-20	98% - 6%	1-20	98% - 7%	1-20	97% - 10%	1-20	97% - 10%	1-20	97% - 10%	1-20	97% - 10%	1-20	97% - 10%		
ELKO	600GLI	230V50Hz	40-600	U	1-20	98% - 1%	1-13	97% - 1%	1-8	96% - 1%	1-8	96% - 1%	1-8	96% - 1%	1-8	96% - 1%	1-8	96% - 1%		
ELKO	420GLEI	230V50Hz	40-420	U	1-14	98% - 1%	1-13	97% - 4%	1-10	97% - 19%	1-10	97% - 19%	1-10	97% - 19%	1-10	97% - 19%	1-10	97% - 19%		









Angaben zum OSRAM Lampentyp

Bewertung der Testergebnisse in Ampel Kategorien. Beinhaltet sowohl die Lampenanzahl als auch den dimmbaren Bereich













## DIMMER COMPATIBILITY PAR16

Legend					PARATHOM PRO PAR16 35 36°	PARATHOM PRO PAR16 50 36°	PARATHOM DIM PAR16 35 36°	PARATHOM DIM PAR16 50 36°	PARATHOM DIM PAR16 80 36°	PARATHOM DIM PAR16 80 60°	PARATHOM DIM PAR16 80 120°	PARATHOM DIM PAR16 100 36°										
Very good dimmability with indicated number of lamps (dimming range greater than 75%)																						
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)																						
Undesired dimmability																						
Not tested																						
					EAN/ Basic Code	EAN/ Basic Code	EAN/ Basic Code	EAN/ Basic Code	EAN/ Basic Code	EAN/ Basic Code	EAN/ Basic Code	EAN/ Basic Code										
					4058075095243 / AC07991 4058075095229 / AC07993 4058075095168 / AC08012	4058075095427 / AC08013 4058075095403 / AC08014 4058075095304 / AC08015	4058075095205 / AC07990 4058075095182 / AC07992 4058075095144 / AC07994	4058075095328 / AC07995 4058075095380 / AC07995 4058075095366 / AC07996 4058075095342 / AC07996 4058075095267 / AC07997 4058075095281 / AC07997	4058075095489 / AC07998 4058075095465 / AC07999 4058075095441 / AC08000	4058075095540 / AC08001 4058075095502 / AC08003 4058075095526 / AC08002	4058075095601 / AC08004 4058075095588 / AC08005 4058075095564 / AC08006	4058075096608 / AC08007 4058075096561 / AC08008 4058075096547 / AC08009										
Dimmer					Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range				
Brand	Model	Voltage range	Power	Type																		
ABB	STD 50-3	230/50Hz	60-500	L	1-11	89-20%	1-3	100-32%	1-13	90-18%	1-7	91-24%	1-2	90-27%	1-2	90-27%	1-2	90-27%	1-8	94-22%		
Altenburger	50,3	230/50Hz			1-20	92-20%	2-20	100-17%	2-20	92-20%	1-18	93-22%	1-20	90-16%	1-20	90-16%	1-20	90-16%				
AURORA	DSP 400	230/50Hz	400	R			1-3	100-0%	3-7	0	1-5	88-0%	1-20	90-26%	1-20	90-26%	1-20	90-26%	1-3	92-0%		
Berker	2861	230/50Hz	50-420	U	1-20	92-33%	1-20	100-34%			3-20	93-32%	1-20	91-30%	1-20	91-30%	1-20	91-30%	1-20	94-27%		
bticino	NT4402N	230/50Hz	500	R			1-12	98-27%			1-11	79-21%	1-5	78-23%	1-5	78-23%	1-5	78-23%	1-6	80-16%		
Bticino	/NT4408HC/HD/HS44C	230/50Hz					1-12	100-0%	3-14	91-0%	2-13	93-16%	2-10	92-0%	2-10	92-0%	2-10	92-0%	1-9	95-0%		
Bticino	L/N/NT4411N	230/50Hz			1-10	79-11%	1-10	99-9%	1-10	79-10%	1-9	80-8%	1-10	80-9%	1-10	80-9%	1-10	80-9%	1-6	82-4%		
Busch-Jaeger	6523 U-102	230/50Hz	40-420	T	1-2	82-29%	1-10	100-37%			1-2	84-28%							1	87-25%		
Busch-Jaeger	6526 U	230/50Hz			1-10	85-31%	1-8	100-37%											1-6	88-26%		
Busch-Jaeger	2250 U	230/50Hz	60-600	L	1-12	92-12%	1-4	100-24%	2-15	92-12%	1-5	92-18%	1-3	93-21%	1-3	93-21%	1-3	93-21%	1-9	95-13%		
Busch-Jaeger	6513 U-102	230/50Hz	420	T	1-20	93-26%	2-20	100-24%	2-20	92-24%	2-20	93-22%	1-20	92-22%	1-20	92-22%	1-20	92-22%	1-20	97-17%		
CENTURY CONTROL	MULTI DIMMER	230/50Hz	60-600	U	1-8	89-13%	1-7	100-17%	2-9	89-14%	1-9	90-11%	1-7	90-15%	1-7	90-15%	1-7	90-15%	1-6	94-7%		
DINUY	RE EL1 LE1	230/50Hz	400	LED	1-10	99-5%	1-7	100-4%	1-9	99-0%	1-7	100-0%	1-7	99-5%	1-7	99-5%	1-7	99-5%	1-5	99-2%		
ELKO	600GLE/I	230/50Hz					1-6	100-0%	1-4	85-0%	1-16	87-21%	1-5	86-0%	1-5	86-0%	1-5	86-0%	1-10	90-0%		
ELKO	400GLI	230/50Hz					1-2	100-2%			1-5	87-0%	1-2	86-2%	1-2	86-2%	1-2	86-2%	1-3	90-2%		
ELKO	420GLE/I	230/50Hz	40-420	U	1-10	85-8%	1-9	100-7%	1-9	84-8%	1-7	86-0%	1-8	85-7%	1-8	85-7%	1-8	85-7%	1-6	88-3%		
ELKO	600GLi	230/50Hz	40-600	U	1-15	87-25%	1-6	100-0%	1-4	85-0%	1-11	87-0%	1-5	88-26%	1-5	88-26%	1-5	88-26%	1-6	91-21%		
ELKO	315GLE	230/50Hz	20-315	T	1-20	91-28%	1-20	100-30%	2-20	91-28%	1-20	92-27%	1-20	90-26%	1-20	90-26%	1-20	90-26%	1-20	95-22%		
ELKO	1000LRI	230/50Hz			1-20	96-0%	1-20	100-0%	1-20	95-0%	1-20	97-0%	1-19	96-0%	1-19	96-0%	1-19	96-0%	1-16	98-0%		
ELKO	630GLE	230/50Hz	20-630	U	1-20	91-17%	1-20	100-15%	1-18	91-17%	1-20	94-18%	1-9	90-15%	1-9	90-15%	1-9	90-15%	1-20	95-11%		
Eltako	EUD61NPN-UC	230/50Hz	5-400	R / L / C	1-10	82-3%	1-7	100-3%	1-8	83-0%	1-8	84-0%	1-4	83-3%	1-4	83-3%	1-4	83-3%	1-6	87-1%		
Feller	40600 RLC	230/50Hz	20-600	U			1-6	100-0%	1-4	85-0%	1-16	87-21%	1-5	86-0%	1-5	86-0%	1-5	86-0%	1-10	90-0%		
Feller	40420.RLC	230/50Hz			1-10	85-8%	1-9	100-7%	1-9	84-8%	1-7	86-0%	1-8	85-7%	1-8	85-7%	1-8	85-7%	1-6	88-3%		
Feller	40600.RL	230/50Hz			1-15	87-25%	1-6	100-0%	1-4	85-0%	1-11	87-0%	1-5	88-26%	1-5	88-26%	1-5	88-26%	1-6	91-21%		
Feller	40200.LEDxxx	230/50Hz			1-20	90-27%	1-20	100-27%	1-20	90-27%	1-20	90-25%	1-20	89-25%	1-20	89-25%	1-20	89-25%	1-20	94-21%		
Feller	40600.RC	230/50Hz			1-20	91-17%	1-20	100-15%	1-18	91-17%	1-20	94-18%	1-9	90-15%	1-9	90-15%	1-9	90-15%	1-20	95-11%		
Feller	31000	230/50Hz			1-20	96-0%	1-20	100-0%	1-20	95-0%	1-20	97-0%	1-19	96-0%	1-19	96-0%	1-19	96-0%	1-16	98-0%		
Gira	030700	230/50Hz	20-525	T	1-20	89-25%	2-20	100-25%	1-20	90-25%	1-20	90-23%	1-20	88-23%	1-20	88-23%	1-20	88-23%	1-20	93-18%		
Gira	117600	230/50Hz	50-420	U	1-20	93-34%	1-20	100-34%			3-20	94-32%	2-20	90-29%	2-20	90-29%	2-20	90-29%	1-20	93-28%		
GIRA	226200	230/50Hz			1-2	91-10%	1	100-14%	1	90-10%	1-4	92-0%	1-2	92-13%	1-2	92-13%	1-2	92-13%	1-3	94-6%		
Gira	238500	230/50Hz											1-20	91-0%	1-20	91-0%	1-20	91-0%	1-20	95-8%		

## DIMMER COMPATIBILITY PAR16

Legend					PARATHOM PRO PAR16 35 36°	PARATHOM PRO PAR16 50 36°	PARATHOM DIM PAR16 35 36°	PARATHOM DIM PAR16 50 36°	PARATHOM DIM PAR16 80 36°	PARATHOM DIM PAR16 80 60°	PARATHOM DIM PAR16 80 120°	PARATHOM DIM PAR16 100 36°								
Very good dimmability with indicated number of lamps (dimming range greater than 75%)																				
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)																				
Undesired dimmability																				
Not tested					EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code								
					4058075095243 / AC07991 4058075095229 / AC07993 4058075095168 / AC08012	4058075095427 / AC08013 4058075095403 / AC08014 4058075095304 / AC08015	4058075095205 / AC07990 4058075095182 / AC07992 4058075095144 / AC07994	4058075095328 / AC07995 4058075095380 / AC07995 4058075095366 / AC07996 4058075095342 / AC07996 4058075095267 / AC07997 4058075095281 / AC07997	4058075095489 / AC07998 4058075095465 / AC07999 4058075095441 / AC08000	4058075095540 / AC08001 4058075095502 / AC08003 4058075095526 / AC08002	4058075095601 / AC08004 4058075095588 / AC08005 4058075095564 / AC08006	4058075096608 / AC08007 4058075096561 / AC08008 4058075096547 / AC08009								
Dimmer					Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range		
Brand	Model	Voltage range	Power	Type																
Gira	217400	230/50Hz	4X20-250	KNX-U	1-20	94-20%	1-16	100-20%	1-14	0	1-20	95-18%	1-19	94-19%	1-19	94-19%	1-19	94-19%	1-17	98-12%
Hager	WUD87	230/50Hz	400	LED-U	1-20	91-26%	1-10	100-20%	1-20	89-22%	1-20	90-20%	1-20	91-20%	1-20	91-20%	1-20	91-20%	1-20	84-15%
Hamilton	KP1X40	230/50Hz	400																	
Hugo Müller	paladin 872110 led	230/50Hz			1-10	99-5%	1-7	100-4%	1-9	99-0%	1-7	100-0%	1-7	99-5%	1-7	99-5%	1-7	99-5%	1-5	99-2%
Jung	225 TDE	230/50Hz			1-20	89-25%	2-20	100-25%	1-20	90-25%	1-20	90-23%	1-20	88-23%	1-20	88-23%	1-20	88-23%	1-20	93-18%
Jung	254 UDIE1	230/50Hz			1-20	93-34%	1-20	100-34%			3-20	94-32%	2-20	90-29%	2-20	90-29%	2-20	90-29%	1-20	93-28%
Jung	225 NVDE	230/50Hz	20-500	L	1-2	91-10%	1	100-14%	1	90-10%	1-4	92-0%	1-2	92-13%	1-2	92-13%	1-2	92-13%	1-3	94-6%
Jung	1224 LEDUDE	230/50Hz		LED									1-20	91-0%	1-20	91-0%	1-20	91-0%	1-20	95-8%
Jung	3904 REGHE	230/50Hz			1-20	94-20%	1-16	100-20%	1-14	91-0%	1-20	95-18%	1-19	94-19%	1-19	94-19%	1-19	94-19%	1-17	98-12%
Legrand	770061	230/50Hz	400	RL			1-8	100-20%	3-19	90-18%	2-8	93-17%	2-4	91-18%	2-4	91-18%	2-4	91-18%		
Legrand	770062	230/50Hz	400	RLC	1-20	92-0%	1-9	100-0%	1-20	93-0%	1-20	94-17%	1-20	91-0%	1-20	91-0%	1-20	91-0%		
Legrand	078405	230/50Hz	600	RL			1-12	100-0%	3-14	91-0%	2-13	93-16%	2-10	92-0%	2-10	92-0%	2-10	92-0%	1-9	95-0%
Legrand	099314	230/50Hz	300	RL			1-6	100-0%	3-4	68-0%	2-6	91-13%								
Legrand	665114	230/50Hz	400	U	1-10	79-11%	1-10	99-9%	1-10	79-10%	1-9	80-8%	1-10	80-9%	1-10	80-9%	1-10	80-9%	1-6	82-4%
Legrand	067083=048869=048	230/50Hz			1-10	79-11%	1-10	99-9%	1-10	79-10%	1-9	80-8%	1-10	80-9%	1-10	80-9%	1-10	80-9%	1-6	82-4%
MASTER	DM-DGL	230/50Hz	1000	U / LED	1-4	95-2%	1-14	100-2%	1-15	96-0%	1-12	97-0%	1	96-3%	1	96-3%	1	96-3%		
MASTER	DM-2500	230/50Hz	2500	U / LED			1-20	100-2%	1-20	96-0%	1-20	98-0%							1-20	99-1%
Merten	MEG 5170-0300	230/50Hz	10-200	U																
Merten	MEG 5140	230/50Hz	9-100	L			1	100-0%	2	81-0%	1-2	83-0%	1	83-0%	1	83-0%	1	83-0%	1-2	85-1%
Merten	MEG5139-0000	230/50Hz					1-6	100-0%	1-4	85-0%	1-16	87-21%	1-5	86-0%	1-5	86-0%	1-5	86-0%	1-10	90-0%
Merten	MEG 5131	230/50Hz	40-400	L			1-6	100-0%	2-3	86-0%	1-9	87-0%	1-6	87-0%	1-6	87-0%	1-6	87-0%	1-6	90-0%
Merten	MEG 5132	230/50Hz					1-6	100-0%	2-3	86-0%	1-9	87-0%	1-6	87-0%	1-6	87-0%	1-6	87-0%	1-6	90-0%
Merten	MEG5138-0000	230/50Hz			1-10	85-8%	1-9	100-7%	1-9	84-8%	1-7	86-0%	1-8	85-7%	1-8	85-7%	1-8	85-7%	1-6	88-3%
Merten	MEG5133-0000	230/50Hz			1-15	87-25%	1-6	100-0%	1-4	85-0%	1-11	87-0%	1-5	88-26%	1-5	88-26%	1-5	88-26%	1-6	91-21%
Merten	MEG5134-0000	230/50Hz			1-20	90-27%	1-20	100-27%	1-20	90-27%	1-20	90-25%	1-20	89-25%	1-20	89-25%	1-20	89-25%	1-20	94-21%
Merten	MEG5137-0000	230/50Hz			1-20	91-17%	1-20	100-15%	1-18	91-17%	1-20	94-18%	1-9	90-15%	1-9	90-15%	1-9	90-15%	1-20	95-11%
Merten	MEG5136-0000	230/50Hz			1-20	91-28%	1-20	100-30%	2-20	91-28%	1-20	92-27%	1-20	90-26%	1-20	90-26%	1-20	90-26%	1-20	95-22%
Merten	MEG 5135	230/50Hz	60-1000	L	1-20	96-0%	1-20	100-0%	1-20	95-0%	1-20	97-0%	1-19	96-0%	1-19	96-0%	1-19	96-0%	1-16	98-0%
MK	K4501	230/50Hz	180	L	1-2	81-13%	1-2	100-14%	1-2	80-14%	1-2	81-15%							1-2	85-11%
NEXUS	881P-01	230/50Hz	400	L	1-2	92-0%	1-3	100-0%			1-6	93-0%							1-4	97-0%

## DIMMER COMPATIBILITY PAR16

Legend					PARATHOM PRO PAR16 35 36°	PARATHOM PRO PAR16 50 36°	PARATHOM DIM PAR16 35 36°	PARATHOM DIM PAR16 50 36°	PARATHOM DIM PAR16 80 36°	PARATHOM DIM PAR16 80 60°	PARATHOM DIM PAR16 80 120°	PARATHOM DIM PAR16 100 36°								
	Very good dimmability with indicated number of lamps (dimming range greater than 75%)																			
	Limited dimmability with indicated number of lamps (dimming range smaller than 75%)				EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code								
	Undesired dimmability																			
	Not tested																			
					4058075095243 / AC07991 4058075095229 / AC07993 4058075095168 / AC08012	4058075095427 / AC08013 4058075095403 / AC08014 4058075095304 / AC08015	4058075095205 / AC07990 4058075095182 / AC07992 4058075095144 / AC07994	4058075095328 / AC07995 4058075095380 / AC07995 4058075095366 / AC07996 4058075095342 / AC07996 4058075095267 / AC07997 4058075095281 / AC07997	4058075095489 / AC07998 4058075095465 / AC07999 4058075095441 / AC08000	4058075095540 / AC08001 4058075095502 / AC08003 4058075095526 / AC08002	4058075095601 / AC08004 4058075095588 / AC08005 4058075095564 / AC08006	4058075096608 / AC08007 4058075096561 / AC08008 4058075096547 / AC08009								
Dimmer					Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range		
Brand	Model	Voltage range	Power	Type																
NIKO	330-0070000701	230/50Hz	5-200	U			1-5	100-14%	1-5	96-13%	1-3	98-12%	1-3	98-12%	1-3	98-12%	1-3	98-12%	1-3	99-8%
NIKO	310-0190001901	230/50Hz	5-200	U	1-20	97-2%	1-15	100-2%	1-15	97-0%	1-3	98-0%	1-14	97-12%	1-14	97-12%	1-14	97-12%	1-14	99-1%
Odace	S520518	230/50Hz					1	100-0%	2	81-0%	1-2	83-0%	1	83-0%	1	83-0%	1	83-0%	1-2	85-1%
Odace	S520515	230/50Hz			1-10	85-8%	1-9	100-7%	1-9	84-8%	1-7	86-0%	1-8	85-7%	1-8	85-7%	1-8	85-7%	1-6	88-3%
Odace	S520511	230/50Hz			1-15	87-25%	1-6	100-0%	1-4	85-0%	1-11	87-0%	1-5	88-26%	1-5	88-26%	1-5	88-26%	1-6	91-21%
Odace	S520512	230/50Hz			1-20	90-27%	1-20	100-27%	1-20	90-27%	1-20	90-25%	1-20	89-25%	1-20	89-25%	1-20	89-25%	1-20	94-21%
Osram	HTI DALI 315 DIM	230/50Hz	20-315	DALI-T	1-20	97-21%	1-20	100-22%	1-20	96-21%	1-20	98-20%	1-15	97-19%	1-15	97-19%	1-15	97-19%	1-20	99-14%
PEHA	435 HAN	230/50Hz	60-600	L	1-13	68-17%	1	100-32%	1	83-19%	1-3	84-24%	2	84-13%	2	84-13%	2	84-13%	1-9	87-17%
Schneider	5170	230/50Hz																		
Schneider	SBD5PL	230/50Hz					1	100-0%	2	81-0%	1-2	83-0%	1	83-0%	1	83-0%	1	83-0%	1-2	85-1%
Schneider	SBD600RCRL	230/50Hz					1-6	100-0%	1-4	85-0%	1-16	87-21%	1-5	86-0%	1-5	86-0%	1-5	86-0%	1-10	90-0%
Schneider	SBD400RL	230/50Hz					1-6	100-0%	2-3	86-0%	1-9	87-0%	1-6	87-0%	1-6	87-0%	1-6	87-0%	1-6	90-0%
Schneider	SBD420RCRL	230/50Hz			1-10	85-8%	1-9	100-7%	1-9	84-8%	1-7	86-0%	1-8	85-7%	1-8	85-7%	1-8	85-7%	1-6	88-3%
Schneider	400GLI	230/50Hz	40-400	T	1-2	82-29%	1-2	100-2%			1-5	87-0%	1-2	86-2%	1-2	86-2%	1-2	86-2%	1-3	90-2%
Schneider	SBD600RL	230/50Hz			1-15	87-25%	1-6	100-0%	1-4	85-0%	1-11	87-0%	1-5	88-26%	1-5	88-26%	1-5	88-26%	1-6	91-21%
Schneider	SBD200LED	230/50Hz	400		1-20	90-27%	1-20	100-27%	1-20	90-27%	1-20	90-25%	1-20	89-25%	1-20	89-25%	1-20	89-25%	1-20	94-21%
Schneider	SBD630RC	230/50Hz			1-20	91-17%	1-20	100-15%	1-18	91-17%	1-20	94-18%	1-9	90-15%	1-9	90-15%	1-9	90-15%	1-20	95-11%
Schneider	SBD315RC	230/50Hz			1-20	91-28%	1-20	100-30%	2-20	91-28%	1-20	92-27%	1-20	90-26%	1-20	90-26%	1-20	90-26%	1-20	95-22%
Schneider	ATTD1000RL	230/50Hz			1-20	96-0%	1-20	100-0%	1-20	95-0%	1-20	97-0%	1-19	96-0%	1-19	96-0%	1-19	96-0%	1-16	98-0%
Shuttle	SDIM-T-LED-500W	230/50Hz	2-500	T & LED-T	1-20	94-17%	1-20	100-16%	1-20	95-19%	1-20	96-17%	1-20	93-15%	1-20	93-15%	1-20	93-15%	1-20	97-11%
Siemens	5TC8 284	230/50Hz	20-525	T	1-20	89-15%	2-20	100-13%	1-20	89-14%	2-7	89-12%	3-20	87-13%	3-20	87-13%	3-20	87-13%	1-20	90-8%
Siemens	5SWG1-528-1AB31	230/50Hz	20-500	KNX-U	1-20	93-0%	1-20	100-0%	1-14	88-16%	1-20	95-0%	1-20	92-0%	1-20	92-0%	1-20	92-0%	1-20	93-0%
VADSBO	LD 220	230/50Hz	1-200	U	1-20	99-4%			1-20	99-0%	1-16	99-0%	1-15	99-3%	1-15	99-3%	1-15	99-3%	1-13	99-2%
VARILIGHT	HQ3W	230/50Hz	400		1-20	93-13%	1-10	100-34%	1-8	94-14%	1-20	95-11%	1-8	79-28%	1-8	79-28%	1-8	79-28%	1-6	82-23%
VARILIGHT	JQP401W	230/50Hz	400	T	1-10	77-6%	1	95-5%	1-8	91-0%	2-5	92-15%	1-2	92-15%	1-2	92-15%	1-2	92-15%	1-3	94-8%
Vimar	20135	230/50Hz	3 - 100	U	1-11	90-12%	1-8	100-11%	1-7	91-13%	1-5	91-11%	1-7	90-11%	1-7	90-11%	1-7	90-11%	1-7	95-8%
ZANO	Z GRID 700	230/50Hz	250	LED	1-20	83-0%	1-20	98-0%	1-20	82-0%	1-20	84-0%	1-19	84-0%	1-19	84-0%	1-19	84-0%		
ZANO	Z GRID 500	230/50Hz	500				1-4	100-0%	1	91-0%	1-6	92-0%	1-3	92-0%	1-3	92-0%	1-3	92-0%	1-4	95-0%
ZANO	WH251	230/50Hz	250		1-2	91-0%	1-3	100-0%	3-4	90-0%	1-3	92-0%	1-3	92-0%	1-3	92-0%	1-3	92-0%	1-3	94-0%
ZANO	WH401	230/50Hz	400	L	1-10	91-0%	1-6	100-0%	3-5	91-0%	1-5	92-0%	1-2	92-0%	1-2	92-0%	1-2	92-0%	1-3	95-0%

**Please Note:**

- The compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment, and the results can vary in certain field applications due to a number of factors. OSRAM does not take over any responsibility, warranty or liability that this results can also achieved by using the devices under other conditions, or when using successor models of the tested devices, or different models of the same manufacturer, or when using other LED lamp types
- The absence of a dimmer from this chart does not necessarily imply incompatibility.
- Please reference the dimmer manufacturer's instructions for installation.
- LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance).
- Subject to change without notice
- Errors and omission excepted
- Always make sure to use the most recent release

**Application Notes:**

- For best dimming results trailing edge dimmer type is recommended.
- Trailing edge type dimmer requires the neutral wire for installation.

**Bitte beachten:**

- Die Kompatibilitätsliste basiert auf Tests, die der Hersteller in einer im Labor simulierten Umgebung durchgeführt hat. Die Ergebnisse können aufgrund verschiedener Faktoren in manchen Praxisanwendungen abweichen. OSRAM übernimmt keinerlei Verantwortung, Garantie oder Haftung dafür, dass diese Ergebnisse tatsächlich mit den Geräten unter anderen Bedingungen, mit Nachfolgemodellen der getesteten Geräte, mit anderen Modellen desselben Herstellers oder bei Verwendung anderer LED-Lampentypen erreicht werden.
- Das Fehlen eines Dimmers in der Abbildung bedeutet nicht, dass ein Dimmer nicht kompatibel ist.
- Lesen Sie stets die Installationsanweisungen des Dimmerherstellers.
- LED-Lampen bestehen aus mehreren elektronischen Komponenten. Unter ungünstigen Bedingungen können diese Störgeräusche erzeugen. Im Resonanzfall können selbst geringe Geräusche einen hörbaren Effekt hervorrufen. Einflussfaktoren können die Installation, die Gestaltung des Lampenträgers, die Leuchte (akustischer Resonanzeffekt), der Dimmer oder der Trafo (Oberschwingungen oder elektronische Resonanz) sein.
- Änderungen vorbehalten.
- Irrtümer und Auslassungen vorbehalten.
- Vergewissern Sie sich, dass Sie stets die aktuellste Version benutzen.

**Anwendungshinweis:**

- Um bestmögliche Dimmergebnisse zu erzielen, wird die Verwendung von Phasenabschnitt-Dimmern empfohlen.
- Phasenabschnitt-Dimmer erfordern bei der Installation einen Neutralleiter.

**LEDVANCE GmbH**

Head Office:

Parkring 29-33  
85748 Garching, Germany  
Phone +49 89 780673-100  
Fax +49 89 780673-XXX  
[www.ledvance.com](http://www.ledvance.com)